



**FLOOR PLAN**  
SCALE 1/8" = 1'-0"

- SYMBOL NOTES:**
- 1 8" THK. 4,000 PSI CONC SLAB @ LOADING DOCK DRIVE - REINF. W/ 6x6:6x6 W.W.M. - SEE ENLARGED PLAN SHEET A-3.0
  - 2 6" THK. 3,500 PSI CONC. SLAB @ DOCK - REINF. W/ 6x6:6x6 W.W.M. ON COMP. FILL.
  - 3 6" THK. 3,500 PSI CONC. @ WAREHOUSE AREA - REINF. W/ 6x6:6x6 W.W.M. & 6 MIL. POLY V.B. OVER 4" STONE BASE.
  - 4 4" THK. 3,500 PSI CONC. @ RETAIL AREA - REINF. W/ 6x6:10x10 W.W.M. OVER 6 MIL POLY V.B. OVER 4" STONE BASE - SEE FINISH SCHEDULE FOR REQUIRED FINISHES - TYP. ALL AREAS.
  - 5 SPLIT/SMOOTH FACE C/W - SEE SECTIONS, DETAILS, & ELEVATIONS FOR TYPE & COLORS REQUIRED - TYP. ALL AREAS. FOAM ALL BUILDING WALLS AS PER SPECIFICATIONS - SEE S-2.0 FOR SEISMIC REINFORCING & FILL.
  - 6 STRUCTURAL COLUMNS - SEE STRUCTURAL DRAWINGS.
  - 7 4" THK. 3,000 PSI CONCRETE WALKS @ BUILDING - COORDINATE W/ SITE / CIVIL DRAWINGS FOR ADDITIONAL DETAIL.
  - 8 CONT. 2x6s @ BASE & CHAIR RAIL LOCATED @ 42" A.F.F. (TOP) - SEE FINISH SCHEDULE - INSTALL TREATED 2xs ONTO BLOCK WALLS.
  - 9 3.5/8" 20 GA. METAL STUDS @ 24" O.C. SPACING W/ C1" x 1" PURLINS + 3.1/2" F-G BATT INSULATION - COVER W/ 5/8" GYP. BD. (TYPE "X" @ TOILETS & JANITOR) - PAINTED - WALLS TO 10'-0" A.F.F. - SEE DETAIL 8 / A-2.0
  - 10 6" - 20 GA. METAL STUDS @ 24" O.C. SPACING W/ [ 1" x 1" PURLINS + 3.1/2" F-G BATT INSUL. - COVER W/ 2 LAYERS OF TYPE "X" 5/8" GYP. BD. - PAINTED - WALLS TO DECK - 2 hr. RATED WALL - SEE DETAIL 7 / A-2.0
  - 11 3.5/8" - 20 GA. METAL STUDS @ 16" O.C. SPACING W/ [ 1" x 1" PURLINS + 3.1/2" F-G BATT INSUL - COVER W/ 5/8" GYP. BD. - PAINTED - SEE DETAIL 6 / A-2.0
  - 12 BOX-IN STRUCTURAL COLUMNS W/ 3.5/8" METAL STUDS & 5/8" GYP. BD. - SEE DETAIL 4 / A-2.0
  - 13 2'-2"w x 3'-6"h 1/4" THK. TEMP GLASS IN WOOD CASE FRAME - ALIGN W/ DOOR HEADS.
  - 14 DRESSING ROOM WALLS TO EXTEND UPTO 8'-0"+/- A.F.F. - CAP W/ 1x PAINTED BOARD.

- 15 INSTALL 3/4" PLYWOOD OR "OSB" WINDOW SILL - COVERED ON ALL SIDES WITH PLASTIC LAMINATE & CAULK TO WINDOW FRAME - COLORS AS SELECTED.
- 16 OVERHEAD CAN DOOR W/ VINYL STRIP DOOR CURTAIN - SEE DOOR SCHEDULE & DOOR TYPES SHEET A-4.0.
- 17 5' x 5' x 4" THK. 3,500 CONC. PAD @ REAR ENTRY - REINF W/ 6x6:10x10 W.W.M.
- 18 SLOPED TOP RETAINING WALL
- 19 END OF CONCRETE WALK
- 20 FRAME CEILINGS @ 9'-0" A.F.F. WITH 8" 18 GA. 800 CSJ @ 24" O.C. ALIGN OVER STUDS & APPLY 5/8" GYP. BD. CLG. (PAINTED) & INSULATE W/ 6" F-G BATTS.
- 21 INSTALL 3/4" HAT CHANNELS ONTO BLOCK WALL & COVER W/ 5/8" GYP. BD. (PAINTED) - SEE SCHEDULE.
- 22 PROVIDE 24" w. x 24" h. HINGED ACCESS PANEL @ 10" A.F.F. - 3/4" PLYWOOD W/ LATCH & WOOD CASING - PAINT OUT TO MATCH WALL.
- 23 SEE TYPICAL FRAMING @ STUDWALLS FOR DOORS SHEET A-4.0
- 24 6" 20 GA. METAL STUDS @ 24" O.C. SPACING W/ C1" x 1" PURLINS + 3.1/2" F-G BATT INSUL. - COVER W/ 5/8" GYP. BD. (PAINTED) SEE DETAILS SHEET A-2.0

- GENERAL NOTES:**
- 1. SEE DOOR SCHEDULE, WINDOW & DOOR TYPES. SEE SHEET A-4.0
  - 2. SEE STRUCTURAL SHEET S-1.0 FOR FOUNDATION PLAN AND CONSTRUCTION JOINT LOCATIONS AT FLOORS.

**FINISH SCHEDULE**

FLOOR	CEILING	CEILING HGT.
BASE	WALLS	
<b>FLOOR:</b>		
01	CONCRETE - POLISHED, SEE SPECIFICATIONS.	
02	12" x 12" x 1/8" VCT - SEE SPECIFICATIONS	
03	CARPET TILES AS SELECTED - SEE SPECIFICATIONS	
<b>BASE:</b>		
10	4" RUBBER COVE	
11	2x6 BASE + 2x6 CHAIR RAIL BUMPER STRIPS @ 42" A.F.F. - CONT. PAINTED - INSTALL TREATED 2xs ONTO BLOCK WALLS.	
12	NONE	

- GENERAL NOTES:**
- 1. EXTEND GYP. BD. ON INTERIOR WALLS FULL HGT - SEE SCHEDULE BELOW
  - 2. PURLINS TO BE INSTALLED IN ALL STUD WALLS @ MIDPOINT, SEE SECTIONS.
  - 3. COORDINATE ALL FINISHES LISTED WITH SPECIFICATIONS & ARCHITECT.
- WALLS:**
- 20 INTERIOR MASONRY WALLS, PAINTED PER SPECIFICATIONS.
  - 21 5/8" GYP. BD. PRIME + TWO COATS LATEX SEMI-GLOSS AS PER SPECIFICATIONS.
  - 22 FRP PANELS ON FRAME WALLS TO CEILING OVER 5/8" MOISTURE RESISTANT GYP. B. D.
- CEILING:**
- 30 EXPOSED OPEN CEILINGS - PAINTED (DRY FOG WHITE)
  - 31 5/8" GYP. BD. - PAINTED FINISH.
- CEILING HGT.:**
- 40 15'-4" @ EXPOSED OPEN CEILING TO DECK SLOPES TO 13'-4" @ REAR WALL.
  - 41 9'-0" @ GYP. BD. CEILINGS.

DATE: 02/29/2008  
 COMM. NO.: 070815V2  
 DRAWN BY: STONE  
 CHECKED BY: WILLIAMS

NOTES:  
 THESE DRAWINGS ARE PROTECTED UNDER FEDERAL COPYRIGHT LAWS. PERMISSION IS GRANTED TO REPRODUCE THESE DRAWINGS FOR THE PROJECT ONLY. ALL OTHER REPRODUCTION IS PROHIBITED WITHOUT WRITTEN PERMISSION OF THE ARCHITECT.

STATE OF SOUTH CAROLINA  
 DENNIS WILLIAMS  
 LINCOLTON, NC 27888  
 REGISTERED ARCHITECT

DENNIS F. WILLIAMS, A.I.A.  
 P.O. DRAWER 1159 704/732-4515  
 126 E. SYCAMORE LINCOLTON, N.C. 28092

A NEW FACILITY FOR:  
**GOODWILL INDUSTRIES**  
 SUMMER S.C.

FLOOR PLAN  
 SHEET NO. A-1.0  
 070815FPV4